RABBIT[®] 5000 MICROPROCESSOR REFERENCE

CCESS TAMPER-PROTECTED BYTE

0 = DISABLE USER MODE ACCESS TO AN CH 2 1 = ENABLE USER MODE ACCESS TO AN CH 2

= 0 = DISABLE USER MODE ACCESS TO AN CH 1 1 = ENABLE USER MODE ACCESS TO AN CH 1

 $H_1 = DISABLE USER MODE ACCESS TO AN CH$ 1 = ENABLE USER MODE ACCESS TO AN CH


= DISABLE HANDSHAKE FOR I/O BANK = ENABLE HANDSHAKE FOR I/O BANK

10 = START AT START INPUT FALLING EDGE 11 = START AT START INPUT EITHER EDGE

10 = STOP AT STOP INPUT FALLING EDGE 11 = STOP AT STOP INPUT EITHER EDGE

00 = IGNORE STOP INPUT 01 = STOP AT STOP INPUT RISING EDGE

READ LSB (LATCHES MSB)



RABBIT www.rabbit.com



REGISTER LEGEND Read/Write 📃 Write Only 느 Read Only **Read** (Special Behavior on Write Operation) NOTE: ZERO MUST BE WRITTEN TO ALL UNUSED BITS